

together with the complementary notches of the fastening element makes possible a grid setting of the front attachment member 31 of 2.5 mm or a multiple thereof.--.

In the Claims:

Amend Claims 9 and 16-18.

1. (Withdrawn). A connecting element for an assembly system comprising a plurality of system supports, having openings arranged in a defined spacing on at least one of an outer wall (68.1, 68.2) of the system support, wherein said connecting element (1; 11; 31; 65) comprises a first member (2; 12; 32) and at least one second member (3; 13; 33) with at least one of said first and second members (2; 12; 32.3; 13; 33) having at least one elongated opening (4, 5; 14, 15, 34, 35, 66) with elongated parallel sides and with at least a plurality of notches (6, 7) extending continuously in side-by-side relation over the length of said parallel sides of said parallel sides of said at least one elongated opening with elongated parallel side said notches extending transversally of the length of said elongated opening, said notches arranged for securing said connecting element (1; 11; 31; 65) to said system support or to a base surface by a fastening element (61), passed through the at least one said elongated opening (4, 5; 14, 15, 34, 35; 66), and engageable with complementary notches (69.1, 69.2) of the fastening element (61).

2. (Previously presented and currently amended). A connecting element, as set forth in claim 1 22, wherein said second member (3; 13; 33) is arranged essentially perpendicular to said first member (2; 12; 32).

3. (Withdrawn). A connecting element, as set forth in claim 1, wherein said second member (33) is a connector (33) formed of a profile section with openings (41.1 to 41.4; 51.2, 51.4; 52.1, 52.3) for fixing the support by said fastening elements passable through said openings (41.1 to 41.4; 51.2, 51.4; 52.1, 52.3) in said connector (33).

4. (Previously presented and currently amended). A connecting element as set forth in claim 3 23, wherein ~~said~~ a connector (33) comprises a said base plate (32), and said base plate has said at least one elongated opening (34, 35) with said tooth-like notches (37.1, 37.2) located along the length of said at least one elongated opening (34, 35) for engagement with complementary notches of one said fastening element.

5. (Previously presented and currently amended). A connecting element, as set forth in claim 3 4, wherein an outer contour of said connector (33) is formed complementary to an inner contour of the support so that said support can slide over said connector (33).

6. (Previously presented and currently amended). A connecting element, as set forth in claim 3 4, wherein an inner contour of the connector (33) is shaped complementary to an outer contour of a support so that the support can be inserted into said connector (33).

7. (Currently amended). A connecting element, as set forth in claim 3 4, wherein said connector (33) has a rectangular configuration ~~and the~~ with openings (41.1 to 41.4; 51.2, 51.4; 52.1, 52.3) are arranged parallel to a plane for the passage of a fastening element, with said plane formed through said first member (32) of the connecting element.

8. (Previously presented and currently amended). A connecting element, as set forth in claim 7, wherein a plurality of additional openings (41.1 to 41.4; 51.2, 51.4; 52.1; 52.3) are ~~arranged~~ spaced vertically relative to each other in a plurality of planes parallel to each other.

9. (Withdrawn). A connecting element, as set forth in claim 1, wherein the notches (6, 7; 20, 21; 37.1, 37.2) are arranged on the side of said first and second members facing away from the support.

10. (Withdrawn). A connecting element, as set forth in claim 1, wherein said notches (6, 7; 20, 21; 37.1, 37.2; 70.1, 70.2) comprise teeth.

11. (Withdrawn). A connecting element, as set forth in claim 1, wherein said connecting element (11; 31; 65) has at least one bead (16; 17; 36) extending in the elongated direction of said openings (4, 5, 14, 15, 34, 35).

12. (Withdrawn). A connecting element, as set forth in claim 11, wherein said teeth are arranged in at least one said bead wall of said at least one bead (16, 17, 36).

13. (Previously presented and currently amended). A connecting element, as set forth in claim + 22, wherein a surface zone surrounding at least one said elongated opening has said notches (6, 7).

14. (Canceled).

15. (Currently amended). A connecting element, as set forth in claim + 22, wherein the outer contour of said at least one first or second member (2, 3) is complementary to the outer contour of at least one of the supports capable of being connected with said connecting element (1; 11; 31).

16. (Withdrawn). A connecting element, as set forth in claim + 22, wherein a fastening element (61) for securing a connecting element (65) to a support comprises an elongated screw having a threaded first end segment (64) and

an opposite end rear grip part (63), with complementary notches (69.1;69.2) comprising teeth.

17. (Withdrawn). A connecting element as set forth in claim 16, wherein said fastening element (61) comprises a spring-based pressure mechanism for tensioning said fastening element (61) with said connecting element (65)

18. (Withdrawn). A connecting element, as set forth in claim 2, wherein both said first and second members (2, 3) have at least one said elongated opening (4, 5).

19. (Original). A connecting element, as set forth in claim 3, wherein said second member is formed of a hollow section.

20. (Previously presented). A connecting element, as set forth in claim 4, wherein said base plate (32) is arranged in the same plane as said first member.

21. (Original). A connecting element, as set forth in claim 10, wherein the pitch of said teeth is 2.5 mm.

22. (Currently amended). A connecting element for an assembly system comprising a plurality of system supports having openings arranged in a defined spacing on at least one of a plurality of outer walls of the ~~support~~ system supports, wherein said connecting element (1; 11; 31; 65) ~~comprises a~~ comprising an

elongated first member (2; 12; 32) and at least one elongated second member (3; 13; 33) with spaced elongated sides and with at least one of said first and second members (2; 12; 32; 3; 13; 33) having at least one elongated opening (4; 5; 14; 15; 34; 35; 66) spaced between and inwardly of said elongated sides thereof and extending in the elongated direction thereof ~~and with elongated parallel sides~~ and with at least a plurality of continuous tooth-like notches extending transversely of the length of said elongated opening, said tooth-like notches arranged for securing said connecting element (1; 11; 31; 65) to one of said system support or to a base surface by a fastening element (61) passed through the said at least one said elongated opening (4, 5; 14, 15; 34, 35; 66) and engageable with complementary tooth-like notches (69.1; 69.2) of the fastening element (61), said connecting element has at least one bead corrugation formed therein extending outwardly from a surface of at least one of said first member or second member containing said elongated opening ~~including said at least one elongated opening with said bead having bead walls (18.1, 18.2; 19.1, 19.2) extending in the direction ??? of said elongated opening ??? (14; 15) and said notches comprise teeth arranged in said bead walls (18.1, 18.2; 19.1, 19.2)~~ said corrugation having a first wall generally parallel to and spaced outwardly from the surface containing the elongated opening and first and second side walls extending from said first wall to a surface from which said corrugation extends said first side wall facing said opening and having

tooth-like notches therein complementary to tooth-like notches in one of said supports to which said connecting element is to be secured.

23. (New). An assembly system comprising at least one base plate and vertical supports extending upwardly from said base plate, and connecting elements for connection to said base plate or to one of said vertical supports, said connecting elements each comprising an elongated first member having elongated sides and at least one elongated second member having elongated sides with at least one of said first member and second member having at least one elongated opening with elongated parallel sides thereon and spaced inwardly from said elongated sides thereof, at least a plurality of tooth-like notches extending continuously in side-by-side relation transversely of the lengths of said elongated opening, said tooth-like notches arranged for securing to said base plate or vertical supports by a fastening element passed through the at least one side elongated opening and engageable with complementary tooth-like notches of said base plate or supports.